



# EC-CERTIFICATE OF CONFORMITY

## 0432 –CPD – 0047

In compliance with the Directive 89/106/EEC of the Council of European Communities of 21 December 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to the construction products (Construction Products Directive - CPD), amended by the Directive 93/68/EEC of the Council of European Communities of 22 July 1993, it has been stated that the construction product

### door closers type "ABLOY DC"

controlled door closing devices as detailed on appendix 1,

placed on the market and produced by

**Abloy OY**  
**Wahlforssinkatu 20**  
**FIN-80801 Joensuu**

is submitted by the manufacturer to a factory production control and to the further testing of samples taken at the factory in accordance with a prescribed test plan and that the approved body – MPA NRW - has performed the initial type-testing for the relevant characteristics of the product, the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.

This certificate attests that all provisions concerning the attestation of conformity and the performances described in Annex ZA of the standard

### EN 1154: 2003-04

were applied and that the product fulfils all the prescribed requirements.

This certificate was first issued on 7. July 2004 remains valid as long as the conditions laid down in the harmonised technical specification in reference or the manufacturing conditions in the factory or the FPC itself are not modified significantly

Dortmund, 30. September 2004



Dipl.-Phys. Karrenberg


**Doorcloser variants: ABLOY DC**


---

**Type :** ABLOY DC 250  
**Description :** door closer with hydraulic damping and adjustable latch action  
**Arm :** slide channel  
 slide channel DC 193 und DC 194.  
**Installation :** normal fixing - door leaf fixing on the pull side  
**Size :** 1-5  
**Classification :** 3 8 1/5 1 1 3  
**Remarks :** also possible: door leaf fixing on the push side, transom fixing on the pull or the push side. By use on fire/smoke compartmentation doors, the maximum opening angle of the door must be limited.

---

**Type :** ABLOY DC 240  
**Description :** door closer with hydraulic damping and adjustable latch action  
**Arm :** slide channel  
 slide channel DC 193 und DC 194.  
**installation :** normal fixing - door leaf fixing on the pull side  
**size :** 1-4  
**classification :** 4 8 1/4 1 1 3  
**remarks :** also possible: transom fixing on the push side.

---

**Type :** ABLOY DC 240  
**Description :** door closer with hydraulic damping and adjustable latch action  
**Arm :** projecting arm  
 projecting arm 7190 und 7199.  
**Installation :** normal fixing - door leaf fixing on the pull side  
**Size :** 2-6  
**Classification :** 4 8 2/6 1 1 3  
**Remarks :** also possible: transom fixing on the push side.

---

**Type :** ABLOY DC 241  
**Description :** door closer with hydraulic damping and adjustable latch action  
**Arm :** projecting arm  
 projecting arm 7190 und 7199.  
**Installation :** normal fixing - door leaf fixing on the pull side  
**Size :** 1-5  
**classification :** 4 8 1/5 1 1 3  
**Remarks :** also possible: transom fixing on the push side.

---

